

WEST-MARK

DOT 412 5,000 GALLON VACUUM TRAILER

Barrel Description:

Code: D.O.T. Non-Code 412 Vacuum
Capacity: 5,000 Gallons
Shape: Round, Straight, Cleanbore
Material: Stainless Steel T304 2B
Products: Various Non-Hazardous
Frames: Stainless Steel Construction
Rings: Stainless Steel Sections Fully Welded to Shell
Manhole: T-316 Stainless Steel, 20" ASME, Full Opening with Viton Gasket in Cover
Ladder: Alum. Tubular, w/ West-Mark Heavy Duty Grated Step
Lights/Wiring: Per D.O.T. Specifications
Primary Shutoff: Stainless Steel Secondary Shutoff Mounted on Side of Barrel with 2" Drain-Off
Bleeder Line: 2" Stainless Steel Valve and Pipe
Gauges: (2) 0-60 PSI / 0-30 HG Pressure / Vacuum One at Secondary, One at Top Rear of Tank

Valving: 4" Stainless Steel NVE (NPV4S) Sliding Gate Valve, Camlock & Cap
Suspension: HUTCH #CH9700T, Cast Flange Mount Hangers, for 5" Round Axle
Springs: HUTCH, 355-00, 11,000 lb Capacity 3-Leaf Medium Arch
Axles: Rockwell 5" Round 1/2" Wall, 71-1/2" Track
Brakes: S-Cam, 16-1/2" x 7"
Drums: Outboard Mount Centrifuse Drums
Lining: Nonasbestos
Slack Adjust: Automatic
Wheels: 22.5 x 8.25 Steel
Tires: 275/80R 22.5 Radial Tires
Fenders: Front & Rear Aluminum Contour Fenders with Stainless Steel Fender Pipes. White Poly, Antisail, Antispray Mudflaps with Logo
Paint: (1) Color Imron on All Mild Steel Parts

Brochure may reflect some options; additional options available.



P.O. Box 100
2704 Railroad Avenue
Ceres, CA 95307

(209) 537-4747
(800) 692-5844
Fax (209) 537-1753


WEST-MARK
www.west-mark.com