

XL MGX: EXPANDABLE



- Rear deck expands to 10 feet wide using 6-inch air cylinders
- · Lightweight design for impressive payload capacity
- Tapered front gooseneck design
- Gooseneck fenders double as loading ramps
- · Stubbed beaver tail at rear
- · Prep for rear loading ramps
- Walking beam suspension



ENABLING YOU TO HAUL MORE

Featuring a capacity of 100,000 pounds in 16 feet, and a base weight of 15,000 pounds, the MGX is sure to deliver many hauling options for the toughest loads. Enjoy the loading advantages of the 21 feet and 4 inches of clear deck space as well as the ability to load onto the gooseneck with fender ramps.

TRANSPORT OPTIONS FOR EVERY STATE

The rear deck of the XL MGX expands from 102 inches wide to 120 inches wide using two 6-inch air cylinders, eliminating an over width return trip. The kingpin settings are compliant with California's kingpin law. This is especially beneficial for drivers in the Western US, yet it also offers flexibility across the country. Custom lengths available for a variety of applications.

DESIGNED FOR YOU. BUILT TO LAST.

CAPACITY

capacity: 100,000 lb overall concentrated: 100,000 lb in 16'

OVERALL LENGTH & WIDTH

overall length: 44' overall width: 102"

GOOSENECK

10' 5" tapered front gooseneck removable gooseneck 50" 5th wheel height 98" 84" swing clearance 16" 30" king pin setting ramps filled with Apitong 1 pair chain hook on gooseneck 1 pair micronova lights

MAIN DECK

23' 1" long (21' 4" clear deck)
(2) 15" fabricated i-beams
23" loaded deck height
8" ground clearance
2" Apitong decking - raised
center deck open
formed cross members
on 24" centers
6 bent d-rings per side
flatback outrigger brackets only
beam tapers to 10.5"
6' steel bucket well pan w/ 6 d-rings
ramp rest at front to utilize
rear ramps

MAIN DECK OPTIONS

additional bent d-rings 2" x 10" Apitong outrigger planks swing out outriggers on 24" centers aluminum front ramps steel front ramps

REAR DECK

10' 6" long
stubbed beaver tail with traction aids
32" loaded deck height
expands from 102" wide to 120" wide
(2) 6" air cylinders to expand
and retract wheel area
40" bolsters between axles
1 pair chain hook on inside of beam
1 pair chain hook on outside of beam
1 chain slot per side

REAR DECK OPTIONS

4" amber strobe as third tail light steel rear loading ramps additional clearance lights aluminum rear ramps

SUSPENSION

walking beam

AXLES

(4) 25,000 lb nominal, trunnion axles69" axle spacing2S1M with air brakes on 4 axles

AXLE OPTIONS

hubometer dust shields disc brakes

WHEELS & TIRES

6.75 x 17.5 steel rims 235 / 75R / 17.5 tires

WHEEL & TIRE OPTIONS

PSI tire inflation system aluminum polished wheels aluminum milled wheels

LIGHTING

12V sealed Grote harness rubber mounted LED lights 2 tail light package 2 clearance lights per side 1 mid-turn light per side 7 pole electric socket

PAINT

black, IH red, CAT yellow, white air & electric done after paint

PAINT OPTIONS

non-standard paint colors non-standard metallic paint

WARRANTY

2 year structural3 year paint1 year parts

AVAILABLE MODELS

XL 100 MGX: Expandable