



Dimensions:

A = 8' 6" (102") B = 22' 1" (265.0") C = 6' 2" (74") D = 16' (192") E = 4 Degree Load Angle Clearance of deck at transport height = 11"

Specifications and Features (Base Trailer)

Ground to Travel Height GVWR 17,650 lbs. Payload Maximum 14,000 lbs. Trailer Weight 3,650 lbs. 4 to 1 Payload to Trailer Weight Ratio Tires L6 T235/85R16LRG (3,750 lbs. Capacity Each) Steel Wheels Cylinders 3-1/2" Diameter x 12" Stroke Adjustable Ball Hitch 2-5/16" Diameter Ramp Built-in Larger Lockable Storage Compartment Controlled Descent

Loads:

425 lbs. Tongue Load (Trailer) 2,250 lbs. Tongue Load (Cargo) 2,650 lbs. Total Tongue Load 806 lbs. Wheel Load (Trailer) 2,944 lbs. Wheel Load (Cargo) 3,750 lbs. Total Wheel Load Two (2), 7,500 lbs. Axles

Tie Down Rail Built-in DC Electric/Hydraulic Pump Tongue Jack Six (6) "D" Rings Breakaway Kit with Chains Electric Brakes Both Axles LED Lighting with 7 Pin Connector Single Pin Grounded 12 VDC Power Cable Control Switch with Cable HSLA Steel Construction (No Angle or Channel Iron) Grade 55 - 3/16" Diamond Plate Flooring Combination Hydraulic/Rubber Suspension

Options

On-Board Power – includes Battery,	
Charger & Maintainer	12784
Cargo Winch 8,000 lbs.	12785
Pintle Hitch (2-1/2" Lunette)	12782
Remote Power Option	12783
(Cord in addition to On Board Power)	

Spare Tire, Wheel & Carrier	12543
Special Paint	12789
(Black, Yellow or Blue Standard)	