


**Dimensions and Loads**



**Dimensions:**

- A = 8' 6" (102")
- B = 22' 1" (265.0")
- C = 6' 2" (74")
- D = 16' (192")
- E = 4 Degree Load Angle
- Clearance of deck at transport height = 11"

**Loads:**

- 425 lbs. Tongue Load (Trailer)
- 3,300 lbs. Tongue Load (Cargo)
- 3,725 lbs. Total Tongue Load
- 825 lbs. Wheel Load (Trailer)
- 3,300 lbs. Wheel Load (Cargo)
- 4,125 lbs. Total Wheel Load
- Two (2), 8,000 lbs. Axles

**Specifications and Features** (Base Trailer)

- Ground to Travel Height
- GVWR 19,725 lbs.
- Payload Maximum 16,000 lbs.
- Trailer Weight 3,725 lbs.
- 4 to 1 Payload to Trailer Weight Ratio
- Tires LT235/85R16LRG (4,805 lbs. Capacity Each)
- Steel Wheels
- Cylinders 3-1/2" Diameter x 12" Stroke
- 2 -1/2" Pintle Hitch
- Ramp Built-in
- Larger Lockable Storage Compartment
- Controlled Descent
- Tie Down Rail Built-in

- DC Electric/Hydraulic Pump
- Tongue Jack
- Six (6) "D" Rings
- Breakaway Kit with Chains
- Electric Brakes Both Axles
- LED Lighting with 7 Pin Connector
- Single Pin Grounded 12 VDC Power Cable
- Control Switch with Cable
- HSLA Steel Construction (No Angle or Channel Iron)
- Grade 55 - 3/16" Diamond Plate Flooring
- Combination Hydraulic/Rubber Suspension

**Options**

- |  |       |                                      |       |
|--|-------|--------------------------------------|-------|
| On-Board Power – includes Battery,<br>Charger & Maintainer ..... | 12784 | Spare Tire, Wheel & Carrier .....    | 12543 |
| Cargo Winch 8,000 lbs. ....                                      | 12785 | Special Paint .....                  | 12789 |
| Remote Power Option .....  | 12783 | (Black, Yellow or Blue Standard)     |       |
| (Cord in addition to On-Board Power)                             |       | 25K Ball Hitch 2 5/16" Coupler ..... | 15347 |