

STOCK # D00591A

35-TON RGN TRAILER



G.V.W.R.	86,000 lbs. (Capacity 70,000 lbs. in 12 ft. span or greater)
Electrical	Sealco US made sealed wiring harness, lifetime LED lights, amber strobe kit standard
Frame	Four cambered main beams, fabricated with 100 KSI (T1) and 80 KSI high tensile steel.
Side Rail	Full Height Fabricated
Tongue	Hydraulic, removable, non-ground bearing gooseneck with 3 position adjustable load blocks and 89" - 107" available swing clearances. Comes standard set-up for wet line.
Tires	255/70 R22.5 LRH
Floors	Apitong flooring (no center decking)
Coupler	SAE 2" Kingpin (16" Kingpin Setting)
Outriggers	12" Swing Out
Ramps	Wood Filled Front Flip Ramps
Tie Downs	Forged D-rings
Deck Length	24' well standard. Additional Optional Lengths
Deck Height	24" (fully loaded)
Deck Width	102" (Expandable to 126" with outriggers)
Fenders	None
Lower Deck	24' well length
Bucket Well	None
Boom Trough	14" Drop
Brakes	All wheel 16.5" x 7" air brakes, automatic slack adjusters, and 4S/2M ABS

STOCK # D00591A

Wheels	10 hole Steel disc / hub piloted inners and Aluminum Dura-Bright outers
Axles	2 - 25,000 lb. axles (5" round, 5/8" wall thickness) w/ oil bath hubs w/ override straps
Suspension	Air ride suspension
Height Control	Adjustable Height Control Valve
Toolbox	20" x 42" Lockable Lid Toolbox
Finish	Sherwin Williams Premium Acrylic Urethane over a Premium Two Part Epoxy Primer; BLACK
Other	Wide Center bolster with chain slots and flag holder slot. Double outriggers at front of trailer.





Kaufman
Trailers
336-790-6800
www.kaufmantrailers.com

Kaufman
Trailers
336-790-6800
www.kaufmantrailers.com





Kaufman
Trailers
336-790-6800
www.kaufmantrailers.com

Kaufman
Trailers
336-790-6800
www.kaufmantrailers.com

