



P.O.BOX 100
CERES, CA 95307
www.west-mark.com

PHONE: (209) 537-4747
TOLL FREE: (800) 692-5844
FAX: (209) 537-1753

GENERAL

The following equipment shall be a new West-Mark single-axle fuel trailer.

PRODUCT: Diesel Fuel.

VESSEL CODE: Non-Spec.

TANK OPERATING PRESSURE: Atmosphere.

TANK OPERATING TEMPERATURE: 125° F maximum

INTENDED AREA OF OPERATION: Specify _____.

INTENDED USE: Highway only.

TANK/ MANHOLES/ VENTING

- Barrel, 500 gallons T-304 stainless steel 10GA oval, straight.
- Head(s), two (2) each stainless steel 10GA, flat and flanged
- V-rails, Stainless steel Two(2)
- Tank mounted directly to trailer decking.
- Manhole(s), one (1) 20" zinc plated with 10" fill.
- Venting, one (1) pressure actuated emergency venting.

LIGHTS AND WIRING

- Trailer Lighting, L.E.D. to meet D.O.T. specifications.
- Reflectors, per D.O.T.
- Electrical Plug, 7-way male RV type.

PLUMBING

- Internal Valve(s), one (1) emergency valve plumbed to pump.
- Operator, mechanical internal valve operator with emergency release.
- Top Loading, pipe run from fill lid of manhole fill pipe shall be removable for access into tank through manhole.
- **Pump- NONE. (Available as option upon request)**

TRAILER

6,000 LB GVWR SINGLE AXLE TRAILER:

- Frame, Heavy duty steel channel with drawbar and deck.
- Decking, carbon steel diamond plate.
- Bumper, carbon steel
- Axle, one (1) 6,000 lb. with electric brakes.
- Wheel Ends, two (2)
- Springs, two (2) each multi-leaf
- Wheel(s), two (2) steel. Wheels remain the Factory color as per the manufacturer's standard.
- Tire(s), two (2) commercial grade radial.
- Brake System, electric brakes for a single axle trailer.
- Break-Away Kit, electric brake, kit consisting of a break-away switch, trickle charger, and a battery
- **Parking Brake- None. (Available as option upon request)**
- Hitch, one (1) Lunette eye with 3 position adjustability.
- Dolly Jack, one (1) heavy duty retractable w/ wheel mounted to trailer tongue.
- Fenders, two (2) carbon steel, with mud splash-back-plate and black rubber mudflaps.

MODEL # SMALLTLR-F

- Safety Chain, two (2) safety chains with hooks.
- Placards, four (4) vinyl.
- One (1) 20 lb. ABC fire extinguisher(s) shall be provided.
- Paint, all carbon steel fabricated parts Gloss WHITE.
- One (1) Operation and maintenance manual(s) in paper format and one (1) on CD-ROM complete with:
 - Operator & maintenance manual
 - Calibration chart (if applicable)
 - Equipment parts list
 - Misc. vendor literature / manuals
- Road test, vehicle shall be tested by factory.

Any and all Brand Name parts mentioned in specifications above are subject to substitution of an equal part that is of a different brand. Other substitutions may also be made if said substitution does not affect the intended function of the vehicle's mission and is equivalent or an upgrade as determined by West-Mark. All specified dimensions are nominal and may vary slightly.

Warranty, unit shall be free from defects in material and workmanship for a period of ONE (1) year.

F.O.B.:

West-Mark (CAGE: 880W5)

581 Industry Way

Atwater, CA 95301. (F.O.B. destination available as option upon request.)